



28V ULTRA-STARTER 20Ah / UST-2030

The 28V Ultra-Starter 20Ah / UST-2030 is a device developed by **ENERCRAFT** to improve the engine start of airplanes or helicopters, providing clean energy, extending the life of the engines and being capable of operating in any weather and environmental condition.



The **ENERCRAFT** Ultra-Starters were developed by our technicians and engineers

to offer the latest technology in energy storage, with a unique configuration, by combining the best of the Lithium Batteries and the best of the Ultracapacitors, ensuring an unbeatable peak current with a very compact and lightweight unit.

SPECIFICATIONS	UST-2030
AC INPUT	Charges from Single Phase 85-264 Vac, Freq. 47/63 Hz, 2 amps
DC OUTPUT	28.5 Vdc (30.6@full charge) Peak start: 1500 Amp (Standard PHCA 5sec)
	Use as GPU: up to 10 Amps
RECHARGING RATE	45 minutes from full discharge @ 25° C
TEMPERATURE RANGE	- 40° C \leftrightarrow 70° C (in operation) - 50° C \leftrightarrow 85° C (in storage)
DIMENSIONS	426 mm x 327 mm x 236 mm
WEIGHT	13 kg (including cable and AN2551)
CABLE	1.5 mts Standard 3 PINS NATO AN2551 (50mm ²)
PROTECTION	Electronic sensors & Fuses
COOLING	Cooling air system integrated into the equipment



MAIN FEATURES

Incorporates the latest technology



ENERCRAFT patented design First to incorporate Lithium & Ultracapacitor technology Full operation in any weather and environmental condition Peak current is ensured, even in non-ideal charge conditions Extends & preserves the aircraft main battery useful life Supports more engine starts without recharge Provides clean energy and a more efficient engine start True DUAL UNIT. Works as a Starter and as a GPU (10Amp)





Voltage and Battery load % USB connector





Reliable waterproofing NANUK[®]'s patented latching system Robust and Impact resistant Modern design





Lightweight unit "All in one" concept One-handed operation Spring loaded handle Reinforced metal padlock holes



